С

## **41630-SO** 12" Square Top, 6" Deep Side Outlet Specification


Josam series 41630-SO fabricated stainless steel (type 304), 12" square top, 6" deep, with no-hub side outlet, anchor tabs and perforated


С


SS grate (standard).

## **STANDARD GRATE**

FREE AREA =  $42.3 \text{ IN}^2$ MEETS ADA AND HEEL-PROOF REQS.







11 13/16 SQ [300]

## **OPTIONS:**

-FB	Filter basket	-HG	Perf. Half grate	Model	Pipe size	А
-SB	Sediment bucket	-3Q	Perf. 3/4 grate	41632-SO	2"	4.4
-VP	Secured grate	-MG	Mesh, anti-slip grate			[112] 4.1
-50	1/2" primer tap	-LG	Ladder grate	41633-SO	3"	[104]
-BW	Butt-weld outlet (spec. 10, 40, 80)	-SG	Perimeter slot grate			
-т	Threaded outlet	-SPG	Slotted plate grate			
-PFO	Push-Fit outlet	-316	Type 316L material			
-NG	No grate					

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



A WATTS Brand

T: (800) 365-6726 • Josam.com